

TOPCon N type Bifacial Mono-crystalline 610-630Watt

0~+5W POWER TOLERANCE

High efficiency TOPCon N - type solar module



Module characteristics



Strong Mechanical Strength
Pass the wind load test of 2400Mpa and the snow load test of 5400Mpa



Lower attenuation
N-type, good reliability and lower LID/LETID attenuation rate.



PID resistance
The attenuation probability of PID phenomenon is minimized through solar cell production technology optimization and raw material control

Harsh environmental adaptation
Robust design for demanding climate conditions.



Multiple busbar and Half cell technique
More light utilization and current collection capabilities, effectively improving product power output and reliability




Long and reliable quality assurance

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality management system

ISO14001:2015: Environmental management system

ISO45001:2018: Occupational health and safety management system



Linear attenuation of 0.4% per year from the 2nd to 30th year.

12 years material and workmanship warranty
30 years power linear warranty

Electrical Parameters

Model Type	ESM-610T		ESM-615T		ESM-620T		ESM-625T		ESM-630T									
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT								
Maximum Power (Pmax)	610	459	615	463	620	467	625	470	630	473								
Open Circuit Voltage (Voc)	55.33	52.56	55.48	52.70	55.63	52.84	55.78	52.98	55.93	53.12								
Short Circuit Current (Isc)	14.09	11.37	14.16	11.43	14.23	11.48	14.30	11.54	14.37	11.60								
Maximum Power Voltage (Vmpp)	45.66	42.28	45.76	42.49	45.86	42.61	45.96	42.72	46.06	42.83								
Maximum Power Current (Impp)	13.36	10.83	13.44	10.89	13.52	10.95	13.60	11.01	13.67	11.04								
Module Efficiency - η_m (%)	22.02		22.20		22.38		22.56		24.37									
Operational Temperature	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$																	
Maximum System Voltage	1500VDC																	
Maximum Series Fuse Rating	25A																	
Power Tolerance	$0 \sim +3\%$																	
Temperature Coefficient of Pmax	$-0.360\%/\text{C}$																	
Temperature Coefficient of Voc	$-0.260\%/\text{C}$																	
Temperature Coefficient of Isc	$+0.04\%/\text{C}$																	
Nominal Operating Cell Temperature	$45 \pm 2^{\circ}\text{C}$																	
Safety Class	Class II																	
Max Load (Front/back)	5400Mpa/2400Mpa																	

STC: Irradiance 1000W/m²

Cell temperature 25°C

Atmospheric quality = 1.5


NOCT: Irradiance 800W/m²

Ambient temperature 25°C


Atmospheric quality = 1.5

Wind speed 1m/S

Mechanical Diagrams



Curve



Packing Details:

31pcs/pallet

40GP:16 pallets/container, 496pcs/40'HQ

EINNOVA SOLARLINE ENERGY CORP. LIMITED

210000 Nanjing
PEOPLE'S REPUBLIC OF CHINA
TEL: +86-25-8479-2033
Cell: +86-138-13088384
EMAIL : emma.wu@einnova-solarline.com
Website: www.einnova-solarline.com

Specification

Cell type	N type mono crystalline 182mm
Half-cell quantity	156pcs (26x6)
Dimension	2465×1134×35mm
Weight	31kg±3%
Glass	3.2mm, tempered and AR coated
Frame	Silver Anodized Aluminum Alloy
Junction Box	IP68
Cable	1200mm (can be customized)